

## DESCRIPTION

## LOUDSPEAKER

5

## TECHNICAL FIELD

The present invention relates to a loudspeaker mainly used in an acoustic apparatus.

## BACKGROUND ART

10

Firstly, a conventional loudspeaker is described with reference to Fig. 19 showing a top view of a conventional long shaped loudspeaker (especially, a loudspeakers with a large length to width ratio in ~~terms of~~ shape, which ~~are~~ is hereafter generally recited as a “slim loudspeakers”), and Fig. 20 showing a two-directional sectional view in a-lengthwise and a-widthwise directions of the

15

slim loudspeaker.

20

Magnetic circuit 6 shown in Fig. 20 comprises lower plate 6a, ring-shaped magnet 6b, and upper plate 6c. Frame 5 is bonded to the magnetic circuit 6. An outer ~~periphery~~ peripheral portion of diaphragm 2 is bonded to the frame 5 via edge 1, and an inner ~~periphery~~ peripheral portion thereof is bonded to voice coil 3 inserted in magnetic gap 6d of the magnetic circuit 6.

An outer ~~periphery~~ peripheral portion of damper 4 is bonded to the frame 5, and an inner ~~periphery~~ peripheral portion is bonded to the voice coil 3 to support the voice coil 3.

25

As the edge 1 used in such a loudspeaker, there are a “fixed edge” which is formed of an extended potion of a diaphragm material, and a “free edge” using other material. Structurally, the former is formed in one-piece structure using a same paper material as the diaphragm by extending a portion thereof, and a plurality of corrugations that are similar to the outer ~~periphery~~ peripheral portion of the diaphragm are formed to provide compliance. The latter is generally made of urethane foam, foamed rubber or ~~the~~ like materials, which ~~are~~ is formed into a sheet and thermally formed into a predetermined

30

shape such as a corrugation edge and a roll edge.

The edge 1 is required to have two functions, ~~these which are;~~ these which are;

(1) to support the diaphragm 2 so as not to induce troubles in terms of vibration, and also to reproduce sound free from non-linear distortion; and

- 5 (2) to suppress an anti-resonance and a partial resonance of the diaphragm 2, including the edge 1, by absorbing vibration energy of the diaphragm 2 so that the reproduced sound quality is not badly affected by a generation of dip on "output sound pressure level vs. frequency" characteristics of the loudspeaker.

\_\_\_\_\_ To address ~~the this~~ above requirement, the edge 1 is required to have  
10 appropriate stiffness and to be excellent in terms of mechanical internal losses and in-linearity ~~against relative to~~ displacement of the diaphragm 2 due to a driving force. In order to satisfy these requirements, a material of the edge 1, a sectional shape along ~~the a~~ radial direction thereof, and a weight and weight distribution thereof ~~had have~~ been studied.

15 Regarding ~~the a~~ shape and structure of the edge 1, which supports the outer ~~periphery peripheral portion~~ of diaphragm 2, corresponding to various shapes of loudspeakers such as the slim loudspeakers mentioned above, there are problems to be solved. That is, ~~the results of the studies~~ are not satisfactory ~~about~~ with regard to "sectional shape, weight and weight  
20 distribution, and stiffness" in relation to "mechanical internal losses and linearity of displacement ~~against relative to~~ driving force."

In order to address the above problems of ~~the a~~ conventional edge, the present invention provides a loudspeaker having an edge improved in terms of sectional shape, weight and weight distribution and stiffness distribution, taking  
25 into account ~~of a~~ relationship of ~~the~~ displacement linearity of the edge itself and a mechanical impedance of a diaphragm. The loudspeaker of the present invention is excellent in terms of acoustic characteristics such as frequency characteristics, transient characteristics, and distortion characteristics.

## 30 DISCLOSURE SUMMARY OF THE INVENTION

The loudspeaker of the present invention comprises ~~at least a~~ magnetic

circuit, a frame connected to the magnetic circuit, and a diaphragm which is connected to a voice coil ~~with~~ via an inner periphery-peripheral portion of the diaphragm, and is connected ~~with~~ via an outer periphery-peripheral portion of the diaphragm to the frame via an edge. The voice coil is inserted into a  
 5 magnetic gap of the magnetic circuit, and a thickness of a sectional shape of an inner ~~periphery-peripheral~~ portion of the edge is thinner than a thickness of a sectional shape of an outer ~~periphery-peripheral~~ portion of the edge. The edge is made of an elastic resin or a foamed resin.

## 10 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top view of a loudspeaker in one embodiment of the present invention.

Fig. 2 is a two-directional sectional view of the loudspeaker ~~in~~ of Fig. 1.

Fig. 3 is an enlarged sectional view of an edge which is an essential  
 15 portion ~~in~~ of one modification of the present invention.

Fig. 4 is an enlarged view of an edge ~~in~~ of another modification of the present invention.

Fig. 5 is an enlarged view of an edge ~~in~~ of still another modification of the present invention.

20 Fig. 6 is a top view of another loudspeaker of the present invention.

Fig. 7 is a two-directional sectional view of the loudspeaker ~~in~~ of Fig. 6.

Fig. 8 is a two-directional sectional view of yet another loudspeaker of the present invention.

25 Fig. 9 is a two-directional sectional view of still another loudspeaker of the present invention.

Fig. 10 is a two-directional sectional view ~~in~~ of a modification of still another loudspeaker the present invention.

Fig. 11 is a two-directional sectional view of yet another loudspeaker of the present invention.

30 Fig. 12 is a two-directional sectional view ~~in~~ of a modification of yet another loudspeaker the present invention.

Fig. 13 is a top view of ~~other~~another loudspeaker of the present invention.

Fig. 14 is a two-directional sectional view of the ~~other~~another loudspeaker of Fig. 13.

5 Fig. 15 is a top view of ~~other~~another loudspeaker of the present invention.

Fig. 16 is a two-directional sectional view of the ~~other~~another loudspeaker of Fig. 15.

10 Fig. 17 is a two-directional view of ~~other~~another loudspeaker of the present invention.

Fig. 18 is an enlarged sectional view of an edge which is an essential portion of ~~other~~another loudspeaker of the present invention.

Fig. 19 is a top view of a conventional slim loudspeaker.

15 Fig. 20 is a two-directional sectional view of the conventional slim loudspeaker.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(Example 1)

20 ~~The~~A first example of the present invention will be described in the following with reference to Fig. 1 and Fig. 2.

Fig. 1 is a top view of a slim loudspeaker ~~in~~according to the first example of the present invention. Fig. 2 shows cross sections of the loudspeaker in two directions of AO (lengthwise direction) and BO (widthwise direction) in Fig. 1. In Fig. 2, magnetic circuit 6 comprises lower plate 6a, ring magnet 6b, and upper plate 6c. An outer ~~periphery~~peripheral portion of diaphragm 2 is bonded via edge 1 to frame 5 which is bonded to the magnetic circuit 6, and an inner ~~periphery~~peripheral portion of the diaphragm 2 is bonded to voice coil 3 inserted into magnetic gap 6d of the magnetic circuit 6.

30 An outer ~~periphery~~peripheral portion of damper 4 is bonded to the frame 5, and an inner ~~periphery~~peripheral portion thereof is bonded to the voice

coil 3 to support the voice coil 3.

When a signal current flows in the voice coil 3, a driving force is generated to vibrate the diaphragm 2, thereby radiating acoustic waves corresponding to a wave forms of the signal current. The damper 4 and the edge 1 support the diaphragm 2 together at an upper and a lower positions, and the damper 4 and the edge 1 function so that the diaphragm 2 and the voice coil 3 being are able to vibrate along an axial direction of the loudspeaker in a stable state.

The edge 1 of the present embodiment is made of a foamed resin mainly based on a polyurethane resin that is an elastic resin, and a sectional shape in a radial direction is, as shown in Fig. 2, a roll edge extended upward in an arc shape. Also, the edge 1 is formed so that a thickness of ~~the an inner periphery~~ peripheral portion 12 side bonded to the diaphragm 2 of flexible portion 11 is thinner and a thickness of ~~the an outer periphery-peripheral~~ portion 13 side is thicker. Since ~~the a~~ sectional shape is formed in this way, ~~the a~~ thinner portion that is connected to the diaphragm 2 and mainly vibrates is light-weight, flexible, and low in mechanical impedance, ~~;~~ thus, bad influences on ~~the a~~ vibration mode of the diaphragm become less. At the same time, since the outer ~~periphery-peripheral~~ portion 13 side is thicker, an absorption of vibration energy transferred from the diaphragm 2 is increased, thereby preventing the generation of standing waves in the diaphragm 2. Preventing the generation of standing waves increases an efficiency of medium and high frequency range sounds radiated from the loudspeaker and further greatly improves frequency characteristics, non-linear distortion characteristics, and transient characteristics. Although it is not illustrated in the figures, as an edge modified in shape from the present ~~Example~~example, it is also possible to use an edge with a structure such that ratios of change in thickness from ~~the an inner periphery-peripheral~~ portion to ~~the an outer periphery-peripheral~~ portion are changed according to changes in stiffness in ~~the~~ lengthwise and widthwise directions of the diaphragm. By using this structure, it is possible to further improve the frequency characteristics, non-linear distortion characteristics, and transient

characteristics.

Fig. 3 shows a modification of the present example, showing an enlarged sectional shape of an edge that is an essential portion. ~~The~~A structural difference between the modification and the Example 1 is that, in edge 1a of the modification has a foamed condition where both of independent foam 17a and continuous foam 17b coexist. Due to this structure, the edge 1a has a gas-tight characteristic necessary as an edge, and ~~the~~ movement of gas in the continuous foam 17b increases ~~the~~ mechanical internal losses, and contributes to further improve ~~the~~ frequency characteristics.

Fig. 4 shows another modification of the present example, showing an enlarged sectional shape of an edge that is an essential portion. In this modification, edge 1b has skin layers 18 on both surfaces. ~~The~~Each skin layer 18 of ~~the~~each surface is ~~formed of one-piece construction with the an~~ internal foamed layer without having a clear interface. Thus, the edge 1b ~~becomes~~ having~~exhibits~~ features of being soft and light in weight.

Fig. 5 is still another modification of the present example, showing an enlarged sectional shape of an edge that is an essential portion. In this modification, an expansion ratio is changed so that a density of inner ~~periphery~~ peripheral portion 12, or a bend portion of edge 1c, is higher than a density of an outer ~~periphery-peripheral~~ portion 13. In this way, decrease in ~~a~~ strength of ~~the a~~ thinned inner ~~periphery-peripheral~~ portion is suppressed. As a methods to change the expansion ratio, two or more kinds of resins, varied in an amount of foaming agent blended into the resins for molding, are molded by a multi-color injection molding, or by a press molding, ~~wherein~~ a plurality of resins (generally sheet-formed) varied in ~~the an~~ amount of foaming agent are disposed in a molding die and formed under heat and pressure. Accordingly, ~~in during~~ the press molding, at a portion corresponding to a vicinity of inner ~~periphery-peripheral~~ portion 12, or ~~the a~~ bend portion, a resin less in ~~the an~~ amount of foaming agent is disposed.

Although ~~the an~~ illustration is omitted, a modification of a roll edge where the flexible portion 11 is bent downward in an arc shape may be used.

For the production of the edge 1a which includes both of the independent foam 17a and continuous foam 17b described above, a foaming thermosetting composition obtained by mechanically mixing gas with a thermosetting composition mainly based on a polyurethane prepolymer and a latent hardener is molded under heat. As the latent hardener, so-called amine adduct, obtained by inactivating solid polyamine, was used in the present example. This is also used in each of the following Examples. However, the latent hardener is not limited to ~~the~~this substance provided that it is dissociated under heat and forms a urethane resin.

Also, the above urethane resin is preferable as a diaphragm support member, taking into account ~~the~~ acoustic performance for ~~the~~ loudspeakers, however, as a material for the edge, it is also possible to use a thermosetting resin and thermoplastic resin composition made of other synthetic resin, thermoplastic elastomer, rubber or foamed resins made of the above resins.

In the present example, a variation of thickness of the edge in the lengthwise direction and that of the edge in the widthwise direction can be varied to improve characteristics. In other words, a thickness ratio of the edge in the lengthwise direction between the inner peripheral portion 12 and the outer peripheral portion 13 is made large to enhance rigidity of the edge in the lengthwise direction, while a ratio of the edge in the widthwise direction is made small. By designing rigidity of these two kinds of edges, i.e., a lengthwise direction edge and a widthwise direction edge, in such a way, a total edge unit becomes improved to have excellent rigidity balance to improve frequency characteristics, non-linear distortion characteristics, and transient characteristics.

(Example 2)

Fig. 6 is a top view of a slim loudspeaker in accordance another example of the present invention. Fig. 7 is a sectional view of ~~the~~this loudspeaker in two directions of AO and BO in Fig. 6. In the description of the present example, same component parts as those in ~~the example~~ Example 1

are given same reference numerals, and ~~the a~~ description thereof is omitted.

Edge 1d of the present ~~embodiment~~ example is made of foamed resin mainly based on polyurethane resin ~~as the same~~ as in Example 1, and its flexible portion is divided into a plurality of sections in a circumferential direction with convex portion 14a and concave portion 14b alternately arranged. Further, ~~the a~~ boundary between ~~the~~ adjacent sections crosses the edge 1d at an angle different from ~~the a~~ peripheral direction, and thereby, ~~the a~~ shape smoothly changes from convex to concave without abruptly ~~change~~ changing in shape. In general, a displacement of an edge in a direction of a convexity and in a direction of a concave concavity are reverse in linearity with respect to a driving force, and this causes a generation of non-linear distortion. However, in the present example, since the convex portion 14a and the concave portion 14b are alternately arranged, ~~the~~ generation of non-linear distortion in the reproduced sound reduces because of mutual neutralization of non-linearity. Further, ~~the~~ unnecessary resonance of ~~the a~~ diaphragm is suppressed by the convexities and concave concavities of the edge.

Fig. 8 shows a modification of the present example, showing a half-sectional view in ~~the~~ directions of AO and BO in Fig. 6, ~~it and~~ also shows a sectional shape of edge 1e. The edge 1e is made of foamed resin mainly based on polyurethane resin ~~as the same~~ as in the Example 1, and ~~the a~~ flexible portion of the edge 1e is divided into a plurality of sections with convex portion 14a and concave portion 14b alternately distributed in a circumferential direction as in the present example, and also, ~~the a~~ sectional shape in ~~the a~~ radial direction is formed such that a thickness at ~~the an~~ inner periphery peripheral portion 12 side is thinner, and a thickness at ~~the an~~ outer periphery peripheral portion 13 side thicker ~~as, the same~~ as in Example 1.

Non-linear distortion of the loudspeaker of this modification is reduced, and at the same time, ~~the a~~ portion which is connected to the diaphragm 2 and mainly vibrates is light-weight and flexible, and is low in terms of mechanical impedance, thereby decreasing ~~the a~~ bad influence on ~~the a~~ vibration mode of the diaphragm, ~~as the same~~ in Example 1. At the same time, since the outer



~~periphery-peripheral~~ portion 13 side is thicker, ~~the~~ absorption of vibration energy transferred from the diaphragm 2 is increased, and thus a generation of standing waves in the diaphragm 2 can be prevented. As a result, ~~the~~ this structure increases an efficiency of ~~the~~ medium and high frequency range sounds radiated from the loudspeaker, and further, greatly contributes to improve ~~the~~ frequency characteristics, non-linear distortion characteristics, and transient characteristics.

(Example 3)

Fig. 9 is a sectional view in two directions of AO and BO of ~~other~~ another loudspeaker having the shape of Fig. 6. In the present ~~Example~~ example, a diameter of an inner ~~periphery-peripheral~~ portion 12 of edge 1 made of foamed resin mainly based on a polyurethane resin, ~~as the same~~ in Example 1, is formed smaller than a diameter of an outer ~~periphery-peripheral~~ portion 22 of diaphragm 2. In the loudspeaker of the present ~~Example~~ example, the diaphragm 2 is supported by the edge 1 with inner portion 23 formed inwardly from the outer ~~periphery-peripheral~~ portion 22 thereof. According to ~~the~~ a configuration of the present example, in a case where a same maximum dimension of a frame is employed, it is possible to improve a low frequency range sound reproduction and to increase ~~the~~ efficiency by maximizing an effective area of the diaphragm.

Fig. 10 shows a modification of the present example, showing a sectional view in the same direction as in Fig. 9. As ~~the same~~ in Example 1, ~~the~~ a sectional shape in ~~the~~ a radial direction of edge 1 made of foamed resin mainly based on polyurethane resin is formed, ~~as the same as in the present example,~~ such that a diameter of the inner ~~periphery-peripheral~~ portion 12 is smaller than a diameter of the outer ~~periphery-peripheral~~ portion 22 of diaphragm 2, and the diaphragm 2 is supported ~~with~~ via an inner portion inward from the outer ~~periphery-peripheral~~ portion 22. Further, as shown in the ~~figure~~ Figure 10, the ~~an~~ inner ~~periphery-peripheral~~ portion 12 side bonded to the diaphragm 2 is formed thinner, and ~~the~~ an outer ~~periphery-peripheral~~ portion 13

side is formed thicker. The loudspeaker of this modification can increase the efficiency, and as the same in Example 1, it increases the efficiency of the medium and high frequency range sounds, and further, greatly contributes to improve the frequency characteristics, non-linear distortion characteristics, and transient characteristics.

(Example 4)

Fig. 11 shows a sectional shape in two directions, lengthwise and widthwise directions, of edge 1 bonded to the diaphragm 2 of the a loudspeaker in the present example. In the present example, as the same in Example 1, the flexible portion 11 of an edge made of foamed resin mainly based on polyurethane resin is formed to have corrugated sections with narrow concave corrugations and convex corrugations alternately arranged. A non-linearity of concave corrugations compensates a non-linearity of convex corrugations, thereby decreasing a level of non-linear distortion in a case of small amplitude.

Fig. 12 shows a modification of the present example, showing a sectional shape viewed in two directions of the edge 1. As the same in Example 1, the a sectional shape in the a radial direction of the edge 1 made of foamed resin mainly based on polyurethane resin is formed to have a corrugated shape as the same in the present example. Further, as shown in the Figure 12, the sectional shape of the edge 1 is formed such that a thickness of the an inner periphery-peripheral portion 12 side bonded to the diaphragm 2 is thinner, and a thickness of the an outer periphery-peripheral portion 13 side is thicker. In a case of small amplitude, this modification decreases the a level of non-linear distortion, and as the same in Example 1, it also increases the efficiency at the medium and high frequency range sounds, and further, greatly contributes to improve the frequency characteristics, non-linear distortion characteristics, and transient characteristics.

(Example 5)

Fig. 13 is a top view of a loudspeaker in according to the present

~~Example~~example. Fig. 14 shows a sectional shape in two directions of AO and BO in Fig. 13. In the present ~~Example~~example, as ~~the same~~ in Example 1, in ~~the a~~ lengthwise direction of ~~the flexible~~ portion 11 of ~~the an~~ edge made of foamed resin mainly based on polyurethane resin, a plurality of rib-shaped convex portions (ribs) 15 are provided in a radial direction by increasing resin thickness so as to change ~~the compliance~~ of the edge. The convex portions 15 are intended to prevent a resonance and deformation of ~~the diaphragm 2~~ by balancing with ~~the lengthwise~~ stiffness of the diaphragm 2 and to improve the frequency characteristics.

Also in the present ~~Example~~example, although ~~the an~~ illustration is omitted, it is possible to make a plurality of modifications. For example, possible modifications include a structure in which ~~the edge~~ material is formed thinner at ~~the an~~ inner ~~periphery-peripheral~~ portion 12 side and thicker at ~~the an~~ outer ~~periphery-peripheral~~ portion 13 side, a structure in which a height of the ribs 15 or an effective thickness of edge portion including the height of rib 15 is thinner at the inner ~~periphery-peripheral~~ portion 12 side and thicker at the outer ~~periphery-peripheral~~ portion 13 side, and other various modifications.

(Example 6)

Fig. 15 is a top view of a loudspeaker of the present example. Fig. 16 shows a sectional view in two directions of AO and BO of the loudspeaker in Fig. 15.

In a loudspeaker of the present example, in a lengthwise direction of ~~the flexible~~ portion 11 of ~~the an~~ edge made of foamed resin mainly based on polyurethane resin, as ~~the same~~ in Example 1, rib-shaped convex portions (rib) 16 increased in thickness of resin along ~~the a~~ peripheral direction are partially provided in order to change ~~the compliance~~ of the edge. This structure is intended to prevent ~~the resonance~~ and deformation of ~~the diaphragm 2~~ by balancing with ~~the lengthwise~~ stiffness of the diaphragm 2 and to improve the frequency characteristics.

Also in the present example, although ~~the an~~ illustration is omitted, it is

possible to make a plurality of modifications. For example, a possible example of a modification is such that a thickness of edge material or an effective thickness of an edge portion including ~~the~~ a height of the rib is formed thinner at ~~the~~ an inner ~~periphery-peripheral~~ portion 12 side and thicker at ~~the~~ an outer ~~periphery-peripheral~~ portion 13 side.

(Example 7)

Fig. 17 shows a sectional view in two directions, lengthwise and widthwise directions, of a loudspeaker in the present example. ~~The~~ flexible portion 11 of ~~the~~ an edge made of foamed resin mainly based on polyurethane resin, as ~~the same in~~ Example 1, is partially changed in edge compliance in accordance with a change in ~~the~~ stiffness of ~~the~~ diaphragm 2. To achieve this purpose, a thickness of the flexible portion 11 of the edge is increased in ~~the~~ a lengthwise direction and a thickness is decreased in ~~the~~ a widthwise direction, and the flexible portion 11 is formed so as to smoothly change in terms of thickness. This structure is intended to prevent ~~the~~ resonance and deformation of the diaphragm 2 by balancing with ~~the~~ lengthwise stiffness of the diaphragm 2 and to improve ~~the~~ frequency characteristics.

Also in the present example, although ~~the~~ an illustration is omitted, it is possible to make a plurality of modifications. For example, a possible example of a modification is such that ~~the~~ structure of the present embodiment is combined with a structure wherein ~~the~~ a substantial thickness of the edge portion is formed thinner at ~~the~~ an inner ~~periphery-peripheral~~ portion 12 side and thicker at ~~the~~ an outer ~~periphery-peripheral~~ portion 13 side.

(Example 8)

Fig. 18 is an enlarged sectional view showing a combined structure of diaphragm 2 and edge 1 which are essential portions of ~~the~~ a loudspeaker in the present example. In the present example, when a foaming thermosetting composition, a raw material of the edge 1, is placed in ~~the~~ a molding die and is molded under heat, the diaphragm 2 is insert-molded to combine the edge 1 and

the diaphragm 2.

Due to ~~the~~this insert molding, when assembling the loudspeaker, an assembling cost can be reduced because ~~the~~a step of bonding the edge 1 and the diaphragm 2 can be omitted. Further, both components are uniformly  
 5 connected with each other under sufficient adhesive strength. Moreover, ~~the~~this connection does not increase a weight due to an adhesive agent, and thus, improves ~~the~~ performance of the loudspeaker.

Above described are ~~the~~ representative ~~Examples~~examples and modifications of the present invention, but the present invention is not limited  
 10 to the above structures. For example, in the above ~~Example~~examples, an edge mainly using foamed urethane resin has been described. However, ~~the~~edge-material of the edge is not limited to such material, and it is also possible to use thermoplastic elastomers, rubbers, and the like. Thus, it is possible to use an equivalent material in terms of quality or to change ~~the~~a molding  
 15 method including ~~the~~ die heating methods. Also, it is possible to perform proper change ~~as far~~so long as ~~the~~ requirements for ~~the~~ configurations mentioned in the present invention are satisfied with respect to ~~the~~ structures and shapes, and the advantages described in the following can be obtained by achieving ~~the~~ purposes of the present invention.

20

#### INDUSTRIAL APPLICABILITY

The speaker of the present invention, that is, ~~the~~a loudspeaker employing a diaphragm support mechanism, or an edge, has ~~the~~ following advantages. Namely, the edge having a structure where ~~the~~an inner periphery  
 25 peripheral portion side is thinner and ~~the~~an outer ~~periphery-peripheral portion~~ side is thicker, has low mechanical impedance against the diaphragm and bad influences on ~~the~~a vibration mode of the diaphragm are decreased. At the same time, ~~the~~ vibration energy is absorbed by ~~the~~a thick portion of the outer ~~periphery-peripheral portion side~~, and thus ~~the~~ standing waves of the diaphragm  
 30 ~~is~~are suppressed, and ~~the~~ efficiency of medium and high frequency range sounds radiated from the loudspeaker is increased, and further, ~~the~~this structure

greatly contributes to improve frequency characteristics, non-linear distortion characteristics, and transient characteristics.

### ABSTRACT OF THE DISCLOSURE

The present invention provides a loudspeaker ~~which is excellent in~~  
~~acoustic characteristics such as frequency characteristics and distortion~~  
5 ~~characteristics.~~ Particularly, including an edge 1 ~~is formed in such manner that~~  
a thickness of a sectional shape in a radial direction increases from an inner  
~~periphery-peripheral portion 12 toward an outer periphery-peripheral portion 13.~~  
Due to this structure, a mechanical impedance of the edge 1 ~~against a~~  
diaphragm 2 ~~is decreased and bad influences on a vibration mode of the~~  
10 ~~diaphragm are suppressed, and also, vibration energy is absorbed by the~~ a thick  
portion of the outer ~~periphery-peripheral portion, thereby suppressing standing~~  
waves of the diaphragm. ~~The structure increases an efficiency of the medium~~  
~~and high frequency range sounds radiated from the loudspeaker, and further,~~  
greatly ~~contributes to improve frequency characteristics, nonlinear distortion~~  
15 ~~characteristics, and transient characteristics.~~